

Data Sheet for Article: MX216232CZ

Moulded Case Circuit Breaker Type EN, 3p, 50kA, set up 160A




Technical Data

Net width (mm)	105,00
Net height (mm)	157,00
Net weight (kg)	1,85
EAN	9004840945065
Power loss (W)	30,60
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	70
Device category	circuit breaker
Standard	EN 60947-2
Rated current (A)	160
Rated voltage	< 690VAC
Short circuit switching capacity (400V) (kA)	50
Size type	2
Tripping Unit	Electronic release - Type EN
Poles	3
Pollution degree	3
IP Rating	IP40
Mechanical durability	15000 operation cycles


Technical Data - continued

Rated insulation voltage [U _i] (V)	1000
Rated impulse withstand voltage [U _{imp}] (V)	8000
Rated ultimate short-circuit breaking capacity I _{cu} (kA)	50
Rated service breaking capacity I _{cs} (kA)	50
AC 380/400/415V	50kA (I _{cu}) / 50kA (I _{cs})
AC 440V	50kA (I _{cu}) / 50kA (I _{cs})
AC 500V	40kA (I _{cu}) / 40kA (I _{cs})
AC 660/690V	8kA (I _{cu}) / 8kA (I _{cs})
Electrical endurance (Operation cycle)	
AC 415V, I _n	6000
AC 690V, I _n	1500

Maßbild



Auslösekennlinie



Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Moulded Case Circuit Breaker Type EN, 3p, 50kA, set up 160A		MX216232CZ
Optional Accessories		
Toggle Lever Locking Device for MX2 No lock included in the scope of delivery.		MX290199
Clip Plate 35mm DIN-S for MX2 3 pole Size type 2, Poles 3		MX290213
Communication module Modbus-RTU 24VDC 1.5m		MX290000
Communication module Modbus-RTU 230VAC 1.5m		MX290001
Box Terminal for MX2 10-120mm ² , 1 piece Size type 2, Al/Cu		MX290015
Connection extension 3 pole for MX2, 6 pieces Poles 3, 6 pieces included per item, for 3-pole MX2 (for top and bottom)		MX290019
Terminal Cover short 3 pole for MX2 Poles 3, for top and bottom		MX290780
Terminal Cover long 3 pole for MX2 Poles 3, for top and bottom		MX290783

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Tunnel Terminal 1x35-240mm ² for MX2, 1 piece, max. 200A Size type 2, Al/Cu, current max. 200A, not maintenance-free for Aluminum, attend to connection conditions!! No use in PV applications/frequency inverters permitted!		MX296730
Tunnel Terminal 2x35-120mm ² for MX2, 1 piece, max. 200A Size type 2, Al/Cu, control connection: M4, current max. 200A, not maintenance-free for Aluminum, attend to connection conditions!! No use in PV applications/frequency inverters permitted!		MX296731
Tunnel Terminal 6x10-35mm ² for MX2, 1 piece, max. 200A Size type 2, Al/Cu, control connection: M4, current max. 200A, not maintenance-free for Aluminum, attend to connection conditions!! No use in PV applications/frequency inverters permitted!		MX296732
Rear Connection, 3P for MX2, for both connection sides Size type 2		MX296734
Socket for MX2 3 pole Size type 2, Poles 3		MX296871
Safety release for socket MX2 for thermal release Size type 2		MX296873
Safety release for socket MX2 for electronic release Size type 2		MX296874
Phase separator plates MX2 Size type 2		MX296870
Rotary handle complete, lockable for MX2, thermal release		MX290125
Rotary handle complete, lockable for MX2, electronic release		MX290126
Door Coupling Rotary Handle, for MX2 for thermal release Size type 2, Axle length 50cm		MX290172
Door Coupling Rotary Handle, for MX2 for electronic release Size type 2, Axle length 50cm		MX290173
Mechanical Interlock for MX2 3 pole Size type 2, Poles 3		MX291581
Under Voltage Release 110VAC for MX2, MX3 Size type 2,3		MX299462
Under Voltage Release 220-240VAC for MX2, MX3 Size type 2,3		MX299471
Under Voltage Release 380-415VAC for MX2, MX3 Size type 2,3		MX299473
Under Voltage Release 24VDC for MX2, MX3 Size type 2,3		MX299481

Article Table

DESCRIPTION	COPPER WEIGHT (kg/km)	Order No.
Optional Accessories		
Under Voltage Release 220VDC for MX2, MX3 Size type 2,3		MX299489
Shunt trip 110VAC for MX2, MX3		MX299567
Shunt trip 220-240VAC for MX2, MX3		MX290154
Shunt trip 380-415VAC for MX2, MX3		MX291607
Shunt trip 24VDC for MX2, MX3		MX299736
Shunt trip 220VDC for MX2, MX3		MX299742
Remote Operator 24VDC for MX2 Size type 2		MX299837
Remote Operator 110VAC/110-120VDC for MX2 Size type 2		MX299838
Remote Operator 220-240VAC/220VDC for MX2 Size type 2		MX299832
Remote Operator 380-415VAC for MX2 Size type 2		MX299833
Auxiliary contact 1 CO		MX199411
Alarm contact 1 CO		MX199511
Universal Adapter 250A outgoing conn. top	383	SI321680