

Data Sheet for Article: NLWFXW403S

Emergency luminaire WFX SC LED IP65 3h 230V AC wall surface

Wall surface, with bayonet chain, self-control, Viewing distance: 60m, 230V AC/DC, Note:
Delivery without pictogram - required pictogram NLWFXPIK.. must be ordered separately,
LiFePO4 battery



Technical Data

Net length (mm)	300,00
Net width (mm)	300,00
Net height (mm)	110,00
Net weight (kg)	1,40
Luminaire type	emergency sign luminaire
Self contained - central battery	Self contained luminaire
Function	self controlled
Version	edge luminaire
Design	WFX
Colour	RAL 9003 (white)
Pictogram	Required adhesive pictogram according to ISO 7010 to be ordered separately

Article Table

DESCRIPTION	Order No.
Emergency luminaire WFX SC LED IP65 3h 230V AC wall surface Wall surface, with bayonet chain, self-control, Viewing distance: 60m, 230V AC/DC, Note: Delivery without pictogram - required pictogram NLWFXPIK.. must be ordered separately, LiFePO4 battery	NLWFXW403S
Necessary Accessories	
Adhesive pictogram arrow left for WFX Factory fitted to an emergency luminaire NLWFXW00.., viewing distance: 60m	NLWFXPIKLI
Adhesive pictogram arrow up for WFX Factory fitted to an emergency luminaire NLWFXW00.., viewing distance: 60m	NLWFXPIKOB
Adhesive pictogram arrow right for WFX Factory fitted to an emergency luminaire NLWFXW00.., viewing distance: 60m	NLWFXPIKRE
Adhesive pictogram arrow down for WFX Factory fitted to an emergency luminaire NLWFXW00.., viewing distance: 60m	NLWFXPIKUN
Optional Accessories	
Set 2 accus LiFePO4 3,2V 1,6Ah f. luminaires. w. LEO or LPK LiFePO4 - Lithium-iron phoshpate battery , UN3480 - UN 3480 : Lithium-Ion batteries	NLAKKU3216
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV