

Data Sheet for Article: SR3PDIEM04

PDU Essential Metered; 4xC13; 2xC19; 230V; 16A

Messung pro Phase, inkl. Befestigungswinkel mit Schrauben



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 4xC13 0° IEC Socket 2xC19 90° IEC Socket
- Power Supply: with C20 Built-In Connector
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technical Data

Net length (mm)	437,40
-----------------	--------

Technical Data - continued

Net width (mm)	45,00
Net height (mm)	60,00
Net weight (kg)	1,00
EAN	4057298233050
PRICE	1.288,00
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	45
Rated voltage	230V
IP Rating	IP20
Product type	Metered Essential
Number of sockets	6
Outlet type	4 x IEC320 C13 und 2 x IEC320 C19
Rated current (A)	16
Phases per feed	1
Connection type	C20
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
mounting	Bracket (L-shape)

DESCRIPTION	Order No.
PDU Essential Metered; 4xC13; 2xC19; 230V; 16A Messung pro Phase, inkl. Befestigungswinkel mit Schrauben	SR3PDIEM04