

Data Sheet for Article: SR3PDIPM09

PDU PRO Metered, 36xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 2075 mm

Technical Data

Net length (mm)	2.075,00
Net width (mm)	56,00
Net height (mm)	65,00
Net weight (kg)	6,77
EAN	4057298207938
PRICE	4.299,00
Min. ambient temperature (°C)	0
Max. ambient temperature (°C)	50
Rated voltage	400V
IP Rating	IP20
Product typ	Metered
Number of sockets	42
Outlet type	36 x IEC320 C13 und 6 x IEC320 C19
Rated current (A)	32
Phases per feed	3
Connection type	CEE 32 A red
Protocol	LDAP
	IPv6
	IPv4
	DNS
	SNMPv1
	SSH
	HTTP
	SNMPv3
	SNMPv2
	NTP
	SSH2
	DHCP
	ModBus /TCP
	SMTP
	HTTPS
	SNMP Trap
	Syslog
mounting	Bracket (L-shape)

DESCRIPTION	Order No.
PDU PRO Metered, 36xC13, 6xC19, 400V, 32A Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!	SR3PDIPM09